


**SEALED EK COLLETS
(External Coolant)**

**Nominal diameter collets
(For coolant through application)**



In this type of collets, slots are SEALED with rubber so that collets can be used for coolant through application and can withstand coolant pressure upto 1500 psi (110 bar)

RD SEALED EK	TYPE OF COLLET	BORE DETAILS				TYPE
		ϕd BORE RANGE				
		MM		INCH		
		FROM	To	FROM	To	
RD11 SEALED EK	NEOPRENE	3.0	5.0	1/8	3/16	T/B
		3.0	4.0	1/8	11/64	C/B *
RD16 SEALED EK	NEOPRENE	5.0	7.0	3/16	1/4	T/B *
		8.0	10.0	5/16	13/32	T/B
RD20 SEALED EK	NEOPRENE	3.0	6.0	1/8	1/4	C/B
		7.0	9.0	9/32	3/8	T/B
RD25 SEALED EK	NEOPRENE	3.0	7.0	1/8	1/4	C/B
		8.0	14.0	5/16	35/64	T/B
RD32 SEALED EK	NEOPRENE	15.0	16.0	19/32	5/8	T/B
		3.0	7.0	1/8	1/4	C/B
RD40 SEALED EK	NEOPRENE	8.0	20.0	5/16	3/4	T/B
		3.0	8.0	1/8	5/16	C/B
RD50 SEALED EK	NEOPRENE	9.0	26.0	11/32	1"	T/B
		6.0	10.0	1/4	3/8	C/B
		12.0	32.0	1/2	1 1/4	T/B

* C/B = Counterbore, T/B = Throughbore

Note:

1. RD SEALED EK collets profile is as per RD form A
2. ABOVE EK COLLETS ARE NORMALLY AVAILABLE IN PRECISION RANGE ONLY
3. For Runout details refer page no. 6

Ordering Instruction:

